

MC 300

STEREO POWER AMPLIFIER

McIntosh

The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ METER switch: WATTS or HOLD. POWER switch: OFF/REMOTE or ON.



BACK PANEL: POWER CONTROL jacks: IN and OUT. FUSE. Power cord receptacle. RIGHT and LEFT gold plated speaker OUTPUT terminals. MODE switch: STEREO, MONO BRIDGED or MONO PARALLEL. LEFT and RIGHT LEVEL controls: 1.4V to 2.5V. UNBALANCED RIGHT/MONO and LEFT audio INPUTS. BALANCED RIGHT/MONO and LEFT audio INPUTS.

SPECIFICATIONS: 300w/ch. (600w mono). **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.005%. **Noise and Hum:** -105dBa. **Output Impedance:** 2, 4 and 8 ohms. (1, 2, 4, 8 and 16 ohms in mono). **Damping Factor:** 40 or greater. **Input Impedance:** 20k unbalanced, 40k balanced. **Input Sensitivity:** 1.4v. Sentry Monitor. Power Guard. **Autoformers.** Power requirements 120V at 6 Amps.

CABINET: L 84



MC 300

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 300 -Sold from 1995 - 1998. S/N: LN1001~LN????

Size: 7-1/16"H, 17-1/2"W and 17-1/2"D. **Weight:** 79 lb. **\$4,000.00**