

MCD 12000

SINGLE DISC SACD/CD PLAYER

McIntosh
The Compendium



FRONT PANEL: Glass with LED/fiber-optic illuminated green nomenclature. Illuminated left relative OUTPUT LEVEL meter (DECIBELS). Tube window. Illuminated right relative OUTPUT LEVEL meter (DECIBELS). ⚡ LIGHTS/PUSH-MENU control. IR remote sensor. Disc tray. INPUT control. ⚡ Touch buttons: DISPLAY/TIME, DISC LAYER, ⏪ BACK, NEXT ⏩. Digital display. Touch buttons: ■ STOP, ▶ PLAY/ II PAUSE, OPEN/CLOSE, STANDBY/ON (with indicator). Handles.



BACK PANEL: RIGHT AUDIO OUTPUTS: BALANCED and UNBALANCED. USB Type-B SERVICE port. RS232 port, IR IN port, DATA control IN, POWER CONTROL: OUT and IN. LEFT AUDIO OUTPUTS: BALANCED and UNBALANCED. ⚡ DIGITAL AUDIO INPUTS: COAXIAL 1 and 2/OPTICAL 1 and 2, MCT input, USB Type-B input. ⚡ Power cord receptacle.

AUDIO SPECIFICATIONS: **Disc Formats:** SACD, CD, CD-R/RW and DVD (DATA) and formats such as ACC, AIF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV and WMA. **Fixed Output Level:** 2.0Vrms Unbalanced and 4.0Vrms Balanced.

MCD 12000

SINGLE DISC SACD/CD PLAYER

McIntosh

The Compendium

AUDIO SPECIFICATIONS (continued):

Output Impedance: 600 ohms Unbalanced and Balanced. **Frequency Response:** SACD: 4Hz-40kHz +0.5, -2dB; CD: 4Hz-20kHz \pm 0.5dB. **Signal to Noise Ratio:** better than 110dBA. **Dynamic Range:** better than 100dB. **Harmonic Distortion:** 0.003% @1,000Hz. **Channel Separation:** better than 98dB (1,000Hz).

DIGITAL AUDIO SPECIFICATIONS: Digital Input Format: SPDIF (PCM¹). **Digital Inputs:** Coaxial: 0.5 p-p/75 ohms; Optical: -15dbm to -21dbm (TOS Link); MCT: 0.5V p-p/75 ohms; USB: USB 2.0 Type B Connector. **Digital Input Sampling Rate:** Coaxial: 16, 24-Bit/192kHz, Dolby Digital, DTS; Optical: 16, 24-Bit/192kHz, Dolby Digital, DTS; MCT: SACD, PCM: 16, 24-Bit/44.1kHz to 192kHz; USB: PCM: 16, 24, 32-Bit/44.1kHz to 384kHz; DXD: DXD352.8kHz, DXD384kHz; DSD: DSD64, DSD128, DSD256, DSD512. **Digital Audio Output Format:** Coaxial and Optical: SPDIF (PCM¹), IEC958 44.1kHz to 192KHz/24Bit. **Digital Outputs:** Coaxial; 0.5V p-p/75 ohm, Optical: -15dbm to -21dbm (TOS Link). **Digital Output Sample Rate:** Up to 24-Bit/19kHz for DISC Input only. **DAC complement:** Two ESS SABRE PRO ES9038PRO 32-bit/8-channel DACs with one dedicated to each channel.

GENERAL SPECIFICATIONS: Transport: Twin Beam laser. **Laser Beam Wavelength:** 650 nm (SACD)/790 nm (CD). **Laser Power:** CLASS IIa/CLASS I Has hand remote **HR087**. **Power Requirements:** 120 Volts, at 50 watts.



MCD 12000 - Sold from May 2022 - Current. S/N: ???1001~??????? (? ,???? UNITS)

Size: 7-5/8"H, 17-1/2"W and 19"D. **Weight:** 32.5 lb. **\$12,000.00**