

DA1

DIGITAL AUDIO MODULE

McIntosh

The Compendium



EARLY

MOUNTING PANEL: DIGITAL AUDIO INPUTS: COAXial 1, COAXial 2 ⚡ OPTICAL 1, OPTICAL 2, MCT, USB AUDIO.



LATER

MOUNTING PANEL: DIGITAL AUDIO INPUTS: USB AUDIO, MCT, OPTICAL 2, OPTICAL 1, ⚡ COAXial 2, COAXial 1.

SPECIFICATIONS: 8-channel, 32-bit Digital-to-Analog Converter (DAC) used in Quad Balanced mode; 6 digital inputs consisting of 2 coax, 2 optical, 1 USB and 1 MCT for use with the MCT series of SACD/CD Transports. The coax and optical inputs will decode music up to 24-bit/192kHz for high resolution audio playback; the USB input accepts even higher PCM signals up to 32-bit/384kHz and supports up to DSD256 and DXD 384kHz.

Used with the **MA 5300**, **MA 7200**, **MA 8900**, **MA 9000**, **MAC 7200**, **C 49**.

DA 1 - Sold from 2017 - 2019. S/N: ??1001~?????? (?,???? UNITS)

Size: ?"H, ?"W and ?"D. **Weight:** ? lb. **\$????.00**