

MI 2

MAXIMUM PERFORMANCE INDICATOR / FM MULTIPATH TUNING INDICATOR

McIntosh

The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Display screen. POWER: OFF or ON (with indicator). **7** SCOPE TEST: L & R AUDIO. MULTIPATH, TEST. HORIZONTAL POSITION. VERTICAL POSITION. FOCUS. INTENSITY.



BACK PANEL: Power cord. FUSE. Unswitched AC outlet. MULTIPATH CONTROLS: SIGNAL STRENGTH (VERTICAL), DEVIATION (HORIZONTAL). AUDIO CONTROLS: LEFT GAIN (VERTICAL), RIGHT GAIN (HORIZONTAL). **7** INPUTS: SIGNAL STRENGTH (TP 1). DEVIATION (TP 2). LEFT AUDIO INPUT. RIGHT AUDIO INPUT. LEFT AUDIO OUTPUT. RIGHT AUDIO OUTPUT.

TUBES: 5-6U8, 3RP1, 2-OB2, 6W4.

SPECIFICATIONS: *Sensitivity:* signal strength (vertical) 0.37V/cm; left gain (vertical). *Input:* 0.37V/cm, right gain (horizontal) 0.27V; deviation (horizontal) 0.27V/cm. *Power Requirements:* 120 Volts at 50 watts.

CABINET: L 11 Also fits L 12, L 52, and L 62



MI 2

MAXIMUM PERFORMANCE INDICATOR /
FM MULTIPATH TUNING INDICATOR

McIntosh

The Compendium



MI 2 - Sold from May 1963 - March 1964. S/N: 100Y1~130Y2 (1,029 UNITS)

Size: 5-1/8"H, 15-5/8"W and 11-1/2"D. **Weight:** 22 lb. **\$219.00**