

MC 162

STEREO POWER AMPLIFIER

McIntosh

The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. **Illuminated** POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ METER switch: LIGHTS OFF, WATTS or HOLD. Remote ON indicator. POWER switch: OFF, REMOTE or ON.



BACK PANEL: Power cord receptacle. FUSE. RIGHT and LEFT speaker output connectors. MODE switch: STEREO or BRIDGED. LEFT and RIGHT level controls: 1.4V to 2.5V. UNBALANCED Left and Right INPUTS. BALANCED Left and Right INPUTS. POWER CONTROL jacks: IN and OUT.

SPECIFICATIONS: 160w/ch into 4 ohms or 100w/ch into 8 ohms. (500w mono into 4 ohms or 320w mono into 8 ohms). **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.005%. **Noise and Hum:** -110dBA. **Output Impedance:** 4 or 8 ohms. **Damping Factor:** 100 at 4 ohms or 200 at 8 ohms. **Input Impedance:** 10k unbalanced, 22k balanced. **Input Sensitivity:** .9v. Sentry Monitor. Power Guard. Direct coupled. **Power Requirements:** 120V at 5 Amps.



MC 162

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 162 - Sold from 1998 - 2003. S/N: PD1001~PD????

Size: 5-3/8"H, 17-1/2"W and 18-1/2"D. **Weight:** 42 lb. **\$2,200.00**