

MC 2000

STEREO POWER AMPLIFIER

McIntosh

The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated left and right POWER OUTPUT meters (linear WATTS, DECIBELS and BIAS SET). ⚡ METER switch: LIGHTS OFF, WATTS or HOLD. Remote ON indicator light. POWER switch: OFF, REMOTE or ON. Tubes can be seen through the clear rectangle above the meters. Gold anodized handles.



BACK PANEL: Stainless steel chassis with titanium gold finish. RIGHT audio INPUT: UNBALANCED and BALANCED. Gold plated RIGHT channel OUTPUT terminals for 2, 4, or 8 Ω speakers. POWER CONTROL: IN and OUT. Right channel FUSE 2. Power cord receptacle. Left channel FUSE 1. INPUT switch: 2.5V or 1.2V. MODE switch: BALANCED or UNBALANCED. Gold plated LEFT channel OUTPUT terminals for 2, 4, or 8 Ω speakers. LEFT audio INPUT: UNBALANCED and BALANCED.

SIDE PANELS: (behind covers) Left side: BIAS ADJUSTment: potentiometers (with momentary push-buttons): V4+6L and V5+7L. Right side: BIAS ADJUSTment: potentiometers (with momentary push-buttons): V5+7R and V4+6R.

TUBES: 8-KT88/6550 output, 4-12AX7A, 2-12AT7. Solid state rectifier bridges.

MC 2000

STEREO POWER AMPLIFIER

McIntosh

The Compendium

SPECIFICATIONS: 130w/ch into 2, 4 or 8 ohms. **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.5%. **Noise and Hum:** -100dBA. **Damping Factor:** greater than 18. **Input Impedance:** 20k unbalanced, 40k balanced. **Input Sensitivity:** switched 1.5V or 2.5V for rated power. *Sentry Monitor.* Unity coupled.



MC 2000 - Sold from 1999 - 2000. S/N: SAC001~SAC781 (780 UNITS)

Size: 11"H, 17-3/4"W and 18-3/4"D. **Weight:** 135 lb. **\$15,000.00**