

MC 207

SEVEN CHANNEL POWER AMPLIFIER

McIntosh

The Compendium



FRONT PANEL: LED/fiber-optic illuminated green/gold nomenclature. 3 POWER GUARD lights – left front, center and right front. Three illuminated POWER OUTPUT meters (linear WATTS or DECIBELS): 1-LEFT FRONT, 4-CENTER, and 7-RIGHT FRONT. ⚡ 4 POWER GUARD lights – left surround, right surround, left back surround and right back surround. Remote ON indicator light. ⚡ METER LIGHTS switch: OFF or ON. POWER switch: OFF, REMOTE or ON.



BACK PANEL: Speaker OUTPUTS connectors: Right Front/channel 7, Right Back/channel 6, Left Back/channel 5. ↗ center/channel 4. ↗ Left Front/channel 1, Left surround/channel 2, right surround/channel 3. ⚡ Polished stainless steel chassis. Power cord receptacle. CIRCUIT BREAKER. INPUTS: channel 7 balanced, channels 7 and 6 unbalanced, channels 6 and 5 balanced, channels 5 and 4 unbalanced, channels 4 and 3 balanced, channels 3 and 2 unbalanced, channels 2 and 1 balanced, channel 1 unbalanced. MULTICHANNEL 25 pin INPUT connector.

SPECIFICATIONS: Seven channels. **200w/ch** into 4 or 8 ohms. **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.005%. **Noise and Hum:** -112dBA. **Output Impedance:** 4 or 8 ohms. **Damping Factor:** >60 at 4 ohms or 140 at 8 ohms. **Input Impedance:** 10k unbalanced and 20k balanced. **Input Sensitivity:** 1v w/4ohm, 1.4v w/8ohm, balanced, and 2v w/4ohm, 2.8v w/8ohm. **Dynamic Headroom:** 1.7 dB. *Dynamic Power Manager. Sentry Monitor. Direct coupled. Power Guard.* **Power Requirements:** 120V at 12 Amps.

MC 207

SEVEN CHANNEL POWER AMPLIFIER

McIntosh
The Compendium



MC 207 - Sold from August 2004 - 2021. S/N: XP1001~XP????, WQ1001~WQ????, VQ1001~VQ???? and ACZ1001~ACZ????

Size: 9-7/16"H, 17-1/2"W and 18-3/4"D. **Weight:** 83 lb. **\$6,000.00**