

MC 2150

STEREO POWER AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Gold anodized aluminum/black. LEFT and RIGHT POWER GUARD lamps: LIMIT or NORMAL. SYSTEM TEST digital readout. ⚡ LEFT GAIN control. SPEAKERS switch: OFF or ON. RIGHT/MONO GAIN control. HEADPHONES jack. POWER switch: OFF or ON.



BACK PANEL: LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. MODE switch: STEREO, MONO BRIDGE or MONO PARALLEL. LEFT and RIGHT (MONO) audio INPUT. INPUT LEVEL switch: 2.5V or .75V.

SPECIFICATIONS: 150w/ch. (300w mono). **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.02%. **Noise and Hum:** -95dB. **Output Impedance:** 1, 2, 4, and 8 ohms. (0.5, 1, 2, 4, 8 and 16 ohms in mono). **Damping Factor:** 30 or greater. **Input Impedance:** 50k. **Input Sensitivity:** 0.75v or 2.5v. **Headphone Impedance:** low. Sentry Monitor. Power Guard. *Autoformers.*

CABINET: L 52 Also fits L 11, L 12, and L 62

MC 2150

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 2150 - Sold from September 1982 - 1987. S/N: DA1001~DA1391 (390 UNITS)
Size: 5-7/32"H, 16"W and 14-1/2"D. **Weight:** 58 lb. **\$1,925.00**