

MC 2255

STEREO POWER AMPLIFIER

McIntosh

The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated left and right power level meters (linear WATTS or DECIBELS). METER function lamps: WATTS, HOLD or DECIBELS. SYSTEM TEST digital readout. POWER GUARD lamps: NORMAL or LIMIT. ⚡ LEFT GAIN control. METER RANGE SWITCH: -20, -10, 0, WATTS and HOLD. HEADPHONES jack. SPEAKERS switch: OFF or ON. RIGHT/MONO GAIN control. POWER switch: OFF or ON. PANLOC buttons.



BACK PANEL: LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. MODE switch: STEREO, MONO BRIDGE or MONO PARALLEL. LEFT and RIGHT (MONO) audio INPUT. INPUT LEVEL switch: 2.5V or .75V. Panloc mounting.

SPECIFICATIONS: 250w/ch. (500w mono). **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.02%. **Noise and Hum:** -95dB. **Output Impedance:** 1, 2, 4 and 8. (0.5, 1, 2, 4, 8 and 16 ohms in mono). **Damping Factor:** 30 or greater. **Input Impedance:** 50k. **Input Sensitivity:** 0.75v or 2.5v. **Headphone Impedance:** low. Sentry Monitor. Power Guard. *Autoformers.*

CABINET: L 54

PANLOC BRACKETS: Right – 043-678 / Left – 043-679

MC 2255

STEREO POWER AMPLIFIER



MC 2255 - Sold from April 1981 - June 1986. S/N: CT1001~CT5700 (4,699 UNITS)
Size: 7-1/8"H, 16-3/16"W and 14-1/2"D. **Weight:** 82 lb. **\$2,995.00**