

# MC 275

STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**CONTROLS & CONNECTORS:** Chrome/black chassis. FUSE. Line OUTPUTS octal socket for 70V/600 OHM output. Speaker OUTPUT: Left and Right barrier strips for 4, 8 and 16 ohms. Input switch: STEREO, TWIN AMP or MONO. GAIN CONTROLS: TWIN AMP, BALANCE and MONO. ⚡ Power cord. 300 W A.C. ONLY outlet. LINE VOLTAGE switch: 117 or 125V. Audio INPUT: STEREO, TWIN and MONO.



McIntosh 275

# MC 275

## STEREO POWER AMPLIFIER

# McIntosh

## The Compendium

**SPECIFICATIONS:** 75w/ch stereo, 150w mono. **Response:** 16Hz-40kHz (+0 -0.1dB). **Distortion:** 0.5%. **Noise & Hum:** -90dB. **Output Impedance:** 4, 8, 16, 67 and 600 ohms. 600 ohm center tap internally grounded. (2, 4, 8, 16 and 32 ohms in mono). **Output voltages:** 25V (isolated), 70.7V (one side grounded) and 230V (center tap grounded). **Internal Impedance:** less than 10% of rated impedance. **Input impedance:** 250k. **Input sensitivity:** 0.5V (in mono or twin amp). 2.0V in stereo. *Unity Coupled.*

**TUBES:** 4-KT88/6550 output, 1-12AX7, 2-12AU7, 2-12AZ7, 2-12BH7. Solid state rectifier bridge.





# MC 275

STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**MC 275** - Sold from May 1961 - 1970. S/N: 10,001~10,147 & 100E1~572E9 (8,610 UNITS)  
**Size:** 8"H, 12-1/4"W and 17-1/4"D. **Weight:** 76 lb. **\$444.00**