

MC275 [MK IV] GOLD

STEREO POWER AMPLIFIER

McIntosh
The Compendium



CONTROLS & CONNECTORS: Polished stainless steel/black chassis. LEFT and RIGHT speaker OUTPUT barrier strips for 4, 8 and 16 OHMS. Left and Right (MONO) audio XLR BALANCED INPUTS jacks. Left and Right (MONO) UNBALANCED LEVEL controls: 2.5V to 1.0V. ⚡ POWER switch OFF or ON. Left and Right (MONO) audio UNBALANCED INPUTS. MODE switch: MONO or STEREO. INPUTS switch: BALANCED or UNBALANCED.




SPECIFICATIONS: 75w/ch stereo into 4, 8 or 16 ohms, 150w mono into 2, 4, or 8 ohms. **Response:** 20-20kHz (+0 -0.2dB). **Distortion:** 0.5%. **Noise & Hum:** -100dB (A weighted). **Output Impedance:** 4, 8, 16 ohms. (2, 4, and 8 ohms in mono), 25V line. **Damping Factor:** greater than 14. **Input Impedance:** 100k unbalanced, 180k balanced. **Input Sensitivity:** 1.2V unbalanced, 2.5V balanced. *Unity Coupled.* **Power Requirements:** 120V at 6.3 Amps.

TUBES: 4-KT88/6550 output, 3-12AX7A, 4-12AT7. Solid state rectifier bridge.

MC 275 [MK IV] GOLD

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC275 [MK IV] GOLD features: 1. PCB wiring. 2. Stainless steel chassis with gold finish. 3. 450 v power supply. Same design as **MC275 [MK IV]**.

MC275 [MK IV] GOLD "Spotting features": 1. Power on-off switch. 2. Gain controls. 3. Unbalanced inputs right-center on the vertical front. 4. Power cord and fuse are on the rear panel. 5. Gold finish. 6. Silver McIntosh 275 emblem.

MC275 [MK IV] GOLD - Sold from 200? - ? 200?. S/N: VR1001~VR????

Size: 8-1/4"H, 12"W and 16-1/2"D. **Weight:** 67 lb. **\$?,000.00**