

MC275 [MK III]

STEREO POWER AMPLIFIER

McIntosh
The Compendium



CONTROLS & CONNECTORS: Stainless steel/black chassis. LEFT and RIGHT speaker OUTPUT barrier strips for 4, 8 and 16 OHMS. Left and right (MONO) audio XLR BALANCED INPUTS jacks. Left and Right (MONO) UNBALANCED LEVEL controls: 2.5V to 1.0V. ⚡ Power cord. POWER switch OFF or ON. FUSE. MODE switch: MONO or STEREO. INPUTS switch: BALANCED or UNBALANCED. Left and Right (MONO) audio UNBALANCED INPUTS.



SPECIFICATIONS: 75w/ch stereo, 150w mono. **Response:** 20-20kHz (+0 -0.2dB). **Distortion:** 0.5%. **Noise & Hum:** -100dB (A weighted). **Output Impedance:** 4, 8, 16 ohms. (2, 4, and 8 ohms in mono), 25V line. **Damping Factor:** greater than 10. **Input Impedance:** 100k unbalanced, 180k balanced. **Input Sensitivity:** 1.0V unbalanced, 2.0V balanced. **Unity Coupled.** **Power Requirements:** 120V at 6.3 Amps.

TUBES (sold separately): 4-KT88/6550 output, 3-12AX7A, 4-12AZ7. Solid state rectifier bridge.

MC275 [MK III] STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC275 [MK III] features: 1. Hybrid PCB/Point-to-point wiring. 2. Stainless steel chassis. 3. 450 v power supply. 4. Same design as CE.

MC275 [MK III] "Spotting features": 1. No **Gordon Gow Commemorative Edition** badge. 2. Gain controls. 3. Unbalanced inputs on far right-hand side of the vertical front. 4. Power cord and fuse are on the vertical front. 5. Convenience outlet on vertical front panel.

MC275 [MK III] - Sold from 1997 - 1998. S/N: E?????~E????? (??0 UNITS)

Size: 7-1/2"H, 12"W and 16"D. **Weight:** 67 lb. **\$4,000.00**