

MC 7150 (& MC 7150W)

STEREO POWER AMPLIFIER

McIntosh
The Compendium



EARLY

FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated LEFT and RIGHT POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ LEFT GAIN control. METER switch: WATTS or HOLD. POWER switch: ON or OFF. RIGHT GAIN controls. PANLOC buttons on early units.



EARLY

BACK PANEL: AC outlet. FUSE. Power cord. LEFT and RIGHT speaker OUTPUT barrier strips. LEFT and RIGHT audio INPUTS. Panloc mounting on early units.

SPECIFICATIONS: 150w/ch into 8 ohms. **Response:** 20-20kHz (+0 -0.25dB).
Distortion: 0.005%. **Noise and Hum:** -110dBa. **Output Impedance:** 2, 4 or 8 ohms. **Damping Factor:** 40 or greater. **Input Impedance:** 20k. **Input Sensitivity:** 1.4v. Sentry Monitor. Power Guard. *Autoformers.*

CABINET: L 52 Also fits L 11, L 12, and L 62

PANLOC BRACKETS: Right – 003-923 / Left – 003-924

MC 7150 (& MC 7150W)

STEREO POWER AMPLIFIER

McIntosh
The Compendium

In 1992, **McIntosh** increased the faceplate width of many of their products. The production cycle of the **MC 7150** spanned this change.

Early production units had the 16-3/16" wide faceplate. Later production units had the 17-1/2" faceplate with no **Panloc** buttons.



EARLY



LATE

In order to allow the customer to have a unified width for various units, a "transition" faceplate was produced and made available to **McIntosh** dealers. This faceplate was 17-1/2" wide and attached to the early chassis with special brackets. Holes were provided in the faceplate for the **Panloc** buttons.



EARLY WITH TRANSITION FACEPLATE

MC 7150 - Sold from 1991 - 1995. S/N: FZ1001~FZ???? (**MC 7150**) and
S/N: GM1001~GM???? (**MC 7150W**)

Size: 5- 5/16"H, [Front panel width was 16-3/16" for early units (**MC 7150**) and 17-1/2" for later units (**MC 7150W**)]. 15-1/4"D. **Weight:** 58 lb. **\$2,400.00**