

# MC 7200 (& MC 7200W)

## STEREO POWER AMPLIFIER

**McIntosh**  
The Compendium



EARLY

**FRONT PANEL:** Glass with illuminated teal/gold nomenclature and lower anodized black aluminum panel. LEFT and RIGHT POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ LEFT GAIN control. METER HOLD switch. POWER switch. RIGHT/MONO GAIN control. PANLOC buttons.



EARLY

**BACK PANEL:** MODE switch: STEREO or MONO. INPUT SENSITIVITY switch: 1.4V or 2.5V. UNBALANCED audio INPUTS: LEFT and RIGHT/MONO. ⚡ FUSE. AC outlet. Left and Right MONO speaker OUTPUT barrier strip. BALANCED audio INPUTS: LEFT and RIGHT/MONO. Panloc mounting.

**SPECIFICATIONS:** 200w/ch into 8 ohms. 300w into 4 ohms. (600w into 8 ohms mono). **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.005%. **Noise and Hum:** -105dBA. **Output:** Direct coupled for 4 to 8 ohms. **Damping Factor:** 200 or greater. **Input Impedance:** 20k unbalanced, 40k balanced. **Input Sensitivity:** 1.4v or 2.5v. Sentry Monitor. Power Guard. Direct coupled.

**CABINET:** L 54 NARROW Also fits L 14 and L21 L52W (WIDE MC 7200)

**PANLOC BRACKETS:** Right - 0??-??? / Left - 0??-???

In 1992, **McIntosh** increased the chassis and/or faceplate width of many of their products. Concurrently, the **Panloc** mounting system was phased out. The production cycle of the **MC 7200** spanned this change.

Early production units had the 16-3/16" wide faceplate. Later production units had the 17-1/2" faceplate.

# MC 7200 (& MC 7200W) STEREO POWER AMPLIFIER

**McIntosh**  
The Compendium



EARLY



EARLY



LATE



**MC 7200** - Sold from March 1989 - 1993. S/N: FA1001~FA???? (**MC 7200**) and  
S/N: GN1001~GN???? (**MC 7200W**)

**Size:** 7-1/8"H, [Front panel width was 16-3/16" for early units (**MC 7200**) and 17-1/2" for  
later units (**MC 7200W**)]. 15-5/8"D. **Weight:** 53 lb. **\$2,779.00**