

# SL 1

## POWERED SUBWOOFER

McIntosh  
The Compendium



**FRONT PANEL:** Power switch with indicator lights: off or on/standby. High pass frequency control: 50 to 125Hz with labels at 50, 63, 80, 100 and 125Hz. Subwoofer frequency control: 50 to 125Hz with labels at 50, 63, 80, 100 and 125Hz. Level control: 0 to max. Control mode switch: variable or THX. Phase switch: 0 or 180.

**BACK PANEL:** High input barrier strip. R/Mono input connector. Line input. Hi pass output. THX/mono. Power control connectors: in and out. Fuse.

**AMPLIFIER:** 250w into 4 ohms. **Distortion:** .005%. **Hum and Noise:** -115dBA. **IHF Dynamic Headroom:** 1.1dB. **Input Sensitivity:** THX 0.1V, variable mode 0.4V (9.0V max). **Input Impedance:** 15k. *Power Guard.*

**LOUDSPEAKER:** one 12" **LD/HP** Front facing woofer. **Frequency Response:** 20-350Hz (THX mode).

**OTHER:** Black ash or walnut veneer. Magnetic-shielding. **THX** approved.

**SL 1** - Sold from 1997 - 2001. **S/N:** NJ1001~NJ???? (? ,???? UNITS)

**Size:** 18-3/4"H, 16-1/2"W and 19"D. **Weight:** 85 lb. **\$2,000.00**