

TM 1

AM - FM STEREO TUNER MODULE

McIntosh

The Compendium



TM 1 MOUNTED IN C 45 PRE-AMP

FM TUNER SPECIFICATIONS: **Useable Sensitivity:** 14dBf or 1.4uV across 75 ohms. **50dB Quieting Sensitivity:** 35dBf or 15uV across 75 ohms, stereo; 19dBf or 2.4uV across 75 ohms, mono. **Signal To Noise Ratio:** 70dB, stereo; 75dB, mono. **Frequency Response:** 20-15kHz (+0/-1dB), stereo or mono. **Harmonic Distortion:** 0.45% in stereo, .3% in mono. **Intermodulation Distortion:** 0.45% in stereo, .25% in mono. **Capture Ratio:** 1.2dB. **Image Rejection:** 75dB. **Alternate Channel Selectivity:** 75dB. **Stereo Separation:** 45dB at 100Hz & 1,000Hz, 35dB at 10,000Hz. **SCA Rejection:** 65dB.

AM TUNER SPECIFICATIONS: **Sensitivity:** 20uV External Antenna Input. **Signal To Noise Ratio:** 58dB at 100% modulation; 48dB at 30% modulation. **Harmonic Distortion:** 0.5% maximum at 50% modulation. **Frequency Response:** 50-6kHz NRSC. **Adjacent Channel Selectivity:** 45dB minimum IHF. **Image Rejection:** 65dB minimum from 540 to 1600kHz. **IF Rejection:** 80dB minimum.

TM 1 - Sold from 2001 - 2010. S/N: SH1001~SH????

Size: 4-1/2"H, 6"W and 3/4"D. **Weight:** 2 lb. **\$500.00**