

# MT 2 TURNTABLE



**TOP PANEL:** LED/fiber-optic illuminated green/gold nomenclature. Power and speed selector: **45, 33, OFF**. Tone arm lift.



**BACK PANEL:** RIGHT and LEFT audio OUTputs. Ground binding post. 45 RPM and 33 RPM fine speed adjustment openings. DC IN 12 V power input.



# MT 2

## TURNTABLE

McIntosh  
The Compendium

**MT2 TURNTABLE SPECIFICATIONS:** *Playback Speeds:* 33 1/3 rpm and 45 rpm.  
*Motor Type:* DC Stainless Steel Brushes. *Speed Control:* Servo System.

**CARTRIDGE SPECIFICATIONS:** *Cartridge Type:* Moving Coil, High Output. *Output Level:* 2.5 mV at 5 cm/s. *Load Impedance:* 1000 ohms recommended (Preamp MC Input). *Frequency Response:* 20Hz to 50,000Hz. *Channel Separation:* 35dB at 1kHz. *Channel Balance:* Less than 0.5 dB at 1kHz. *Tracking Force Range:* 1.6 to 2.0 grams. *Recommended Tracking Force:* 2 grams. *Compliance:* 15 x 10<sup>-6</sup> cm/dyne. *Total Mass:* 6.3 grams. *Stylus:* Elliptical Diamond. *Cantilever Material:* Aluminum.



**MT 2** - Sold from April 2018 - Current. S/N: AFS1001~AFS??? (????? UNITS)

**Size:** 5"H (without dust cover), 17-3/16"W and 17"D. **Weight:** 29 lb. **\$4,000.00**