

MT 5 TURNTABLE

McIntosh
The Compendium



FRONT PANEL: Glass with LED/fiber-optic illuminated green/gold logo and model designation. SPEED select switch: 33, 45, 78. POWER switch: OFF, STANDBY or ON.



BACK PANEL: LEFT and RIGHT audio OUTPUTS. GROUND connector. POWER CONTROL: REMOTE IN and REMOTE OUT. SPEED control FINE ADJUSTMENT: 33-1/3RPM, 45RPM and 78RPM. PLATTER LIGHT adjustment. DC IN 12 V connector.



MT5 TURNTABLE SPECIFICATIONS: Playback speeds: 33-1/3 rpm, 45 rpm, 78 rpm.
Motor type: DC Stainless Steel Brushes. Speed Control: Servo System.

MT 5

TURNTABLE

BLUE POINT NO. 2 CARTRIDGE SPECIFICATIONS: Cartridge Type: Moving Coil, High Output. Output level: 2.5 mV at 5 cm/s. Load impedance: 1000 ohms recommended (Preamp MC input). Frequency Response: 20Hz to 50,000Hz. Channel Separation: greater than 35dB at 1kHz. Channel Balance: less than 0.5 dB at 1KHz. Tracking Force Range: 1.6 to 2.0 grams. Recommended Tracking Force: 2.0 grams. Compliance: 15 X 10⁻⁶ cm/dyne. Total Mass: 6.3 grams. Stylus: Elliptical Diamond. Cantilever Material: aluminum.



MT 5 - Sold from May 2013 - Current. S/N: YJ1001~YJ???? (????? UNITS)

Size: 7"H (without dust cover), 17-1/2"W and 19"D. Weight: 31.5 lb. **\$6,500.00**